

US007083416B1

(12) United States Patent Goldenbert

(10) Patent No.: US 7,083,416 B1 (45) Date of Patent: Aug. 1, 2006

(54) CONTAMINANT-TOLERANT BRAILLE PINS

(75) Inventor: Michael Goldenbert, Melbourne

Beach, FL (US)

(73) Assignee: Freedom Scientific, Inc., St.

Petersburg, FL (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/908,960

(22) Filed: Jun. 2, 2005

Related U.S. Application Data

- (62) Division of application No. 10/710,808, filed on Aug. 4, 2004, now Pat. No. 6,902,403.
- (51) **Int. Cl. G09B 21/00** (2006.01)
- (52) **U.S. Cl.** 434/113; 434/114

(56) References Cited

U.S. PATENT DOCUMENTS

3,718,991	Α	*	3/1973	Kafafian	434/113
4,633,121	Α	*	12/1986	Ogawa et al	310/332
5,226,817	A	*	7/1993	Nakajima et al	434/113
5,842,867	Α	*	12/1998	Hong et al	434/114
6.217.338	В1	*	4/2001	Tieman	434/114

* cited by examiner

Primary Examiner—Kurt Fernstrom (74) Attorney, Agent, or Firm—Ronald E. Smith; Smith & Hopen, P.A.

(57) ABSTRACT

A Braille pin has three parts sharing a common longitudinal axis. A first part has a first breadth and includes a rounded tip felt by a user. A second part has a noncircular transverse cross-section and has a breadth greater than the first breadth. A first shoulder is formed by the juncture of the first and second parts. A third part has a third breadth less than the second breadth. A second shoulder is formed at the juncture of the second and third parts. A pinhole has first, second, and third sections that respectively receive the first, second and third parts of the pin. The first shoulder limits upward pin travel by abutting an overhang at the juncture of the first and second pinhole sections. The second shoulder limits downward pin travel by abutting a step at the juncture of the second and third pinhole sections.

1 Claim, 16 Drawing Sheets

